



# PRODUCT STANDARD SPECIFICATIONS

---

## Product Standard Specifications For **Resurfaced Cowhide** Performance Rating = 4.5

---

**Product:** Resurfaced Cowhide  
**Description:** Top Grain, Cowhide, Aniline Dyed  
**Average Hide Size:** 55 – 60 SF  
**Thickness:** 1.1mm (+/- 0.2mm)

### **Testing:**

Meets the following standards:

**Flammability:** (Must be Specified on the PO)  
FAR 25.853(a)(I)(ii) - 12 Second Vertical  
FAR 25.853(a)(I)(i) - 60 Second Vertical  
Cal TB 117  
NFPA 260 Class 1  
BS5852 Crib 5

**Water Spotting:** IUF420 - No Staining

**Crocking:** ASTM D5053 - minimum 3 on AATCC Greyscale

**Federal Blocking:** ASTM D6116 - No Adhesion of Finish

**Arm Rub Welt:** Townsend LM7 - No Finish Break Through

**Wyzenbeek Welt:** Townsend LM13 - No Change in Color

**Adhesion:** Townsend LM5 - No Removal of Finish

**Taber:** ASTM D3884 H18 250g 300 Cycles – No Change in Color

**Accelerated Aging:** Townsend LM2 - minimum 3 on AATCC Greyscale, No Cracking

Revision 1

21 NOV 2016